

WHAT IS CLAIMED IS:

1. A dust cover for a steering shaft attached to an vehicle body in such a way as to be in contact with the steering shaft to provide protection against  
5 dust and muddy water, comprising:

a cylindrical contact member that is to be in sliding contact with said steering shaft while said steering shaft is rotating; and

a cylindrical reinforcement member for  
10 reinforcing said cylindrical contact member provided radially outside the cylindrical contact member,

wherein a low friction material is attached, by coating or baking, to such a portion of said cylindrical contact member that is in contact with  
15 said steering shaft, or said cylindrical contact member itself is made of a low friction member.

2. A dust cover for a steering shaft according to claim 1, wherein said low friction material is one  
20 of a fluorine series resin, molybdenum, graphite and Teflon.

3. A dust cover for a steering shaft according to claim 1 or 2, wherein said dust cover is provided  
25 with a sealing lip portion that is in contact with said steering shaft to provide sealing function.

4. A dust cover for a steering shaft according to claim 1 or 2, wherein a bellows portion having elasticity is provided between said cylindrical reinforcement member and a portion attached to the vehicle body.

5. A dust cover for a steering shaft attached to a vehicle body in such a way as to be in contact with the steering shaft to provide protection against dust and muddy water, comprising:

a cylindrical contact member that is to be in sliding contact with said steering shaft while said steering shaft is rotating,

wherein a low friction material is attached, by coating or baking, to such a portion of said cylindrical contact member that is in contact with said steering shaft, or said cylindrical contact member itself is made of a low friction member.

6. A dust cover for a steering shaft according to claim 5, wherein said low friction material is one of a fluorine series resin, molybdenum, graphite and Teflon.

7. A dust cover for a steering shaft according to claim 5 or 6, wherein said dust cover is provided with a sealing lip portion that is in contact with

said steering shaft to provide sealing function.

8. A dust cover for a steering shaft according to claim 5 or 6, wherein a bellows portion having  
5 elasticity is provided between said cylindrical contact member and a portion attached to the vehicle body.

9. A dust cover for a steering shaft attached  
10 to an vehicle body in such a way as to be in contact with the steering shaft to provide protection against dust and muddy water, comprising:

a cylindrical metal member that is to be in sliding contact with said steering shaft while said  
15 steering shaft is rotating,

wherein a low friction material is attached, by coating or baking, to such a portion of said cylindrical metal member that is in contact with said steering shaft.

20

10. A dust cover for a steering shaft according to claim 9, wherein said low friction material is one of a fluorine series resin, molybdenum, graphite and Teflon.

25

11. A dust cover for a steering shaft according to claim 9 or 10, wherein said dust cover is provided

with a sealing lip portion that is in contact with said steering shaft to provide sealing function.

12. A dust cover for a steering shaft according  
5 to claim 9 or 10, wherein a bellows portion having elasticity is provided between said cylindrical metal member and a portion attached to the vehicle body.

13. A dust cover for a steering shaft attached  
10 to an vehicle body in such a way as to be in contact with the steering shaft to provide protection against dust and muddy water, comprising:

a cover side cylindrical contact member attached to said dust cover;

15 a cylindrical reinforcement member for reinforcing said cover side cylindrical contact member provided radially outside the cover side cylindrical contact member;

a shaft side cylindrical contact member attached  
20 to said steering shaft that is to be in sliding contact with said cover side cylindrical contact member.

14. A dust cover for a steering shaft according  
25 to claim 13, wherein a low friction material is attached, by coating or baking, to at least one of such portions of said cylindrical contact members at

which they are in contact, or at least one of said cylindrical contact members themselves is made of a low friction material.

5           15. A dust cover for a steering shaft according to claim 14, wherein said low friction material is one of a fluorine series resin, molybdenum, graphite and Teflon.

10           16. A dust cover for a steering shaft according to claim 13 or 14, wherein said dust cover is provided with a sealing lip portion that is in contact with said steering shaft to provide sealing function.

15           17. A dust cover for a steering shaft according to claim 13 or 14, wherein a bellows portion having elasticity is provided between said cylindrical reinforcement member and a portion attached to the  
20 vehicle body.